



FITTING INSTRUCTIONS FOR RYCO CABIN FILTER RCA271P. MERCEDES BENZ E Class W124

1. The cabin air filter is located below the centre section of the engine cowl. It will take anywhere between 45 minutes to 1 hour to complete.

2. Open the bonnet and remove the seal strip on the corners of the cowl, lift up both corners of the rubber trim. Once loose, partially rotate the trim in both directions to loosen it up in the middle where the wiper arm is.

3. Remove the ECU cover behind the battery and lift the windscreen plastic trim so the 4 screws below are easy to reach. Remove all four screws. Now remove the remaining 4 screws on the opposite corner.

4. There are 2 clips, one on each side of the centre half round trim in the middle of the cowl. Pull them out. Proceed to grab the centre mesh from the plastic tab and pull up gently. Then pull the plastic trim up from each corner and remove.

5. The metal centre section has to come out, so remove both screws then remove the other 2 screws located below the wiper arm. Pull out both plastic mesh covers and remove the centre section.

6. Slide out the old cabin air filter out then clean the area and insert the new filter making sure it is in the air flow direction.

7. Refit all components in reverse order.

Ryco Group Pty Ltd 29 Taras Ave Altona North Victoria 3025 Australia. www.rycofilters.com.au RYCO Group A division of GUD NZ Holdings Ltd 626A Rosebank Road Avondale Auckland, New Zealand www.ryco.co.nz