

RYCO CABIN AIR FILTER RCA465M

FITMENT INSTRUCTIONS

GENESIS 01/2020 - ON GV70, GV80, G80 2.5L / GV70 2.0L / GV70 2.2L / GV70 ELEC / GV80 3.0L

FILTER IS LOCATED BEHIND THE GLOVE BOX

- 1 The cabin filter is located right behind the glove box. To get access to the filter it has to be removed. Follow the instructions and it should be a 10 minute job.
- 2 Open your glove box completely. Detatch the rod from side, and twist off both caps from the side wall.
- 3 With the glove box unit out of the way, the cabin filter housing is easily recognisable facing right at you. Proceed to unclip both sides as shown and take it out.



STEP 1



STEP 2



STEP 3





RYCO CABIN AIR FILTER RCA465M

FITMENT INSTRUCTIONS

GENESIS 01/2020 - ON GV70, GV80, G80 2.5L / GV70 2.0L / GV70 2.2L / GV70 ELEC / GV80 3.0L

FILTER IS LOCATED BEHIND THE GLOVE BOX

- 4 Once the filter is out, clean the remaining leaves or dirt from the housing.
- 5 Slide in the new Ryco Filter. The sides of the filter that are firm go in facing the left and right sides of the housing. The soft surface of the filter will face forward. Ensure that the arrow direction is pointing up. In this application the yellow coloured pleat will be facing upwards. Refit all components in reverse order.



STEP 4



STEP 5

