



FITTING INSTRUCTIONS FOR RYCO CABIN FILTER RCA218C.

SAAB 9-5

(Filter is located behind glove box)



- 1. The cabin air filter is located behind the glovebo
- x in the passenger side.
- 2. The glove box unit has to be removed to access the cabin air filter housing. Please follow the steps carefully or refer to the owners manual if unsure.
- 3. Start by unclipping the lower carpet trim attached to the side of the centre console. Pull the carpet trim forward and proceed to remove the screws holding the upper plastic trim righ below the glove box unit in the footwell, carefully pull them and disconnect light connector before removing it completely.
- 4. Remove the three screws holding the bottom section of the glove box. Open the glove box and remove the two screws holding each side then remove the top three screws, close the glove box and gently pull out and disconnect all hoses and connectors to be able to fully remove the glove box.
- 5. Remove the seven bolts holding the cabin air filter housing lid and remove it. Slide the old cabin filter out carefullly to avoid accumulated debris spreading around. Clean the area and insert the new filter making sure it is in the right airflow direction. Refit all components in reverse order.

Ryco Group Pty Ltd 29 Taras Ave Altona North Victoria 3025 Australia. www.rycofilters.com.au RYCO Group A division of GUD NZ Holdings Ltd 626A Rosebank Road Avondale Auckland, New Zealand www.ryco.co.nz